

INDUCTION PYROCERAM COOKING RANGE - 4 AREAS



Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface in CERAN pyroceram, thickness 6 mm. Heating through induction. 4 cooking independent areas. Kettle recognition sensors and automatic check devices. Forced cooling of electronic components. By the electromagnetic induction, pots (minimum Ø 120 mm) of suitable material are required.



Worktop thickness 2 mm

Functional features

- n. 4 independent cooking areas power rated at 5 kW each
- Potentiometer with continuous power regulation from 1 to 10 kW.
- Very low radiation of heat to the environment and greater comfort for the operator, as all the power and heat are supplied to the base of the pan.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking (not with contact) in pans certified for use on induction appliances.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Metal ergonomic knobs with ceramic fiber insulation.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Cooking plate in "CERAN" pyroceram flush and sealed with worktop, 32x67x0.6 cm.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Greater safety in the working area ensured by three sensors positioned underneath the glass ceramic surface to prevent improper operation.
- CE approvals in respect of all current directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

Working voltage	400V 3N ~ 50 ÷60 Hz	Net Weight	50 kg
Gross Weight	55 kg	Electric Power	20 kW
Dimensions	80x92x25 cm	Packing	86x102x116