


Blixer® 3



D

Number of 200-g portions per service



Amount processed per operation

0.3 – 2 kg

A SALES FEATURES

The **Blixer 3** can turn small amounts of cooked or raw ingredients into texture-modified meals (soft, puréed or liquid) in next to no time.

B TECHNICAL FEATURES

Blixer 3. Single-phase. Power: 750 W. Speed 3,000 rpm. 3.7-l stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 2 – 10 portions (200 g).

Select the options you want from the list in Section **F** overleaf.

C TECHNICAL DATA

Output power	750 W
Electrical datas	Single-phase plug supplied
Speed	3,000 rpm
Dimensions (LxWxH)	242 x 304 x 444 mm
Rate of recyclability	95 %
Net weight	14 kg

Supply	Amperage	Reference
230V/50/1	5,5A	33197
230V/50/1 UK plug	5,5A	33198
230V/50/1 DK	5,5A	33200
120V/60/1	13A	33202
220V/60/1	5,5A	33201

MARKING

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006, EN 12852, EN 60529-2000 - IP55 - IP34

E PRODUCT FEATURES/BENEFITS

MOTOR UNIT

- **Industrial direct-drive (no belt) induction** motor designed for intensive use
- Power 750 W
- Stainless-steel motor shaft
- Motor base made from heavy-duty composite material
- Magnetic safety system, thermal failsafe and motor brake
- **Single speed 3,000 rpm**
- **Pulse function** for greater cutting precision

BLIXER® FUNCTION

- **3.7-l stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 3.7-litre bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

Blixer® 3

F OPTIONAL ATTACHMENTS

- Additional bowl, blade assembly, lid and scraper arm unit – Ref. 27337
- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27348
- Additional fine-serrated, twin-blade assembly – Ref. 27347

G DRAWINGS & DIMENSIONS

Single-phase – power cord and plug supplied

