

# PF101S



## Blast chiller freezer-10 trays GN1/1-PULSE

Blast chiller freezer with special functions, 10 GN1/1-EN60x40 containers. Production: 50 kg/cycle +90°C/+3°C and 25 kg/cycle +90°C/+18°C. Temperature range -40°C/+45°C. Functions: blast chilling, freezing, proving and retarder-proving, defrosting and many more. 7" touch display PCB and USB. Probe with 3 sensors, with heating. Preset for connectivity to APOLINK portal. Door opening from right to left



Note \*Product Information (EN17032 – Commission Regulation EU 2015/1095)

### General information

Supplier/producer 's name	SAGI
Series	PULSE
Supplier's model identifier	PF101S
Category	blast chiller-freezer
Type	blast chiller-freezer
Line	catering - pastry&bakery - ice-cream

### Technical features

Temperature range, °C	-40°/+45°C chamber
Yield from +90°C to +3°C (kg)	at product core, 50 - in 90 minutes
Yield from +90°C to -18°C (kg)	at product core, 25 - in 240 minutes
Yield from +65°C to +10°C (kg)	at product core, 50 - EN 22042 test*
Yield from +65°C to -18°C (kg)	at product core, 25 - EN 22042 test*
Energy consumption, kWh/kg	0,078 (chilling) - 0,27 (freezing)
Method for energy consumption	EN 22042
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,15+0,15
LWA dB(A)	64
Valves	thermostatic, liquid line solenoid
Condensation	air - integral cooling unit

Blast chiller freezer-10 trays GN1/1-PULSE

ANGELO PO GRANDI CUCINE S.p.a. con socio unico  
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy  
[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/3 PRINTED 06/11/2024 12:29:43



Defrosting	automatic by heating elements
Fan system control	fan stops when door is opened (from 40% to 100%)
Safety thermostat	cut-off 55°C
Refrigeration power -23,3°C W	935+935
Heating power, W	440+440 - on front of battery for easier maintenance
Frequency/voltage	400V 3N~ / 50Hz
Electric power, kW	1,8

## Construction features

Structure	one-piece structure with rounded corners, with automatic heating of door contact perimeter
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	press-formed, with drain outlet
Insulation thickness, mm	75 - CO2 foam
Door	in AISI 304 stainless steel
Joint de porte	with ten chambers, magnetic, easily replaceable
Standard hinging door	on the right / no-reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	frame in AISI 304 stainless steel - useful for GN 1/1 or EN 60x40 cm containers
Positions (n.)/spaced, mm	10/71,5 - Container insertion direction: side 32,5 cm for GN 1/1; side 40 cm for EN 60x40
Evaporator	copper/aluminium rustproofed evaporator
Easymaintenance	tool-free access to condenser
Safety interlock switch	yes, to stop internal fan
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	#N/D

## Control and functions

Kinf of control	electronic circuit board mounted on door - USB - RS485 communication port
Software Update	with USB pen drive
Display	colour 7" touch screen
Connectivity	with APOLINK accessory for remote control - Industry 4.0
Alarms	optical and acoustical
Languages	IT - EN - ES - DE - FR - NL - DK - PT
Cold functions	Blast-chilling Soft/Hard; Blast-freezing Soft/Hard; Preservation; Precooling; Infinity
Hot functions	Thawing Heater; Proofing; Retarder prover
Special cycles	I.F.R.; Anisakis; Yogurt; Chocolate cake; Precooling
Favourite programs	30: 10 blast-chilling; 10 blast-freezing; 10 retarder prover
HACCP	infinite events up to one year of recording
Alarms (no.)	saving of up to 40 events

# PF101S



## Standard

Core probe	heated, 3 sensors, smart core sensor recognition-mounted on rear of door
Water collection bowl	plastic placed on the outer bottom

## Dimensions and weights

Packing (LxDxH), cm	87x99,6x206
Dimensions (LxDxH), cm	80,2x95,1x178,2
Gross Weight (kg)	200
Net Weight (kg)	175

Blast chiller freezer - 10 trays GN1/1-PULSE

